























































SYMBOL DIRECTORY

	protection class I		voltage (V); frequency (Hz)		modules according to Zhaga standards
	protection class II		windage area		product complies with the applicable requirements
	with Constant Light Output over the entire lifetime		luminaire incl. pole		maximum ambient temperature
	compatible for emergency systems		bracket length		opening for cable outlet for a safe usage of electricity or water with closed doors
	Colour Rendering Index		bracket inclination		door for cable junction box
	protection degree		LEIPZIGER LEUCHTEN stock goods; fast delivery		base segment available with root
	impact resistance		ENEC certified product		

	other luminous fluxes available		other bracket inclinations available		other lenses, modules or light distributions available
	other colour temperatures available		other top entries available		luminaire available in a smaller size
	Colour Rendering Indexes available		glazing made of xxx available		pole, column or tube with root available
	other RAL / DB colours available		glazing made of polycarbonate available		

	surge protection 10kV		other cable or cable lengths available		other heights available
	dimming with or without pilot-line or via DALI interface		other pole heights available		pole powder coated in 2 different colours available
	intelligent light control system		other bracket lengths available		luminaire can be equipped with more spots
	loop in and loop out		add. back shield for asymmetrical light distribution available		non-slip glass available
	intelligent, dynamic and event-controlled light management system		glazing made of xxx available		extra blind for reduction of back light available
	intelligent, dynamic and event-controlled light management system implemented in a separate box for pole mounting		curved glazing available		cover with 1 or 3 windows available
	pole with flange plate		special colours, e.g. "corten steel" powder coating		other beams available
	brackets / other bracket lengths available		heritage pole in other designs available		motion sensors available