


post top - / side entry luminaire



ASL 2010/1 LLM-DA LED



- windage area: 0,105 (on the side) / 0,045 (front)
- recom. pole height: 5,00m – 8,00m
- light standards: low and medium lighting requirements
- lamp: incl. 1 or 2 glare-free LLM-DA LED modules
- colour temperature: 4.000K neutral white or 3.000K warm white
- surge protection: 10kV
- LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency
- LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management
- light control: at extra cost: power reduction, dimming, DALI or CLEVER LIGHT
- optical system: reflector system for directed, horizontally mounted LLM-DA LED Module
- light distribution: wide beam
- luminaire head: made of die-cast aluminium and aluminium; powder coated
- colour: DB 703; other colours on request
- glazing: polycarbonate, clear, impact resistant, UV-stabilised, to be hinged down
- wiring: via a plug and socket connector within the luminaire head
- installation: for top entry \varnothing 76mm and \varnothing 60mm, inclination 5° resp. 10° or for side entry \varnothing 60mm; dispatch standard: for top entry, 5°
- accessory: cable, column, pole accessories, wall, corner or column bracket, back light shield for non-glare on the rear side - to be ordered separately
- application areas: parkways, cycle lanes, residential and local distribution roads, main streets, boulevards, pedestrian zones, car parks, schools, home for elderly people, hotels, factory premises, squares, pedestrian crossings



wide beam
height: 6.00m; area: 30m x 30m

lamp	kg	product code
LLM-DA LED 8W/1,100lm/4,000K	12.7	9.135.8015.41-2
LLM-DA LED 15W/1,800lm/4,000K	12.7	9.135.8005.41-2
LLM-DA LED 24W/3,000lm/4,000K	12.7	9.135.8035.41-2
LLM-DA LED 9W/1,100lm/3,000K	12.7	9.135.8017.41-2
LLM-DA LED 16W/1,800lm/3,000K	12.7	9.135.8008.41-2
LLM-DA LED 26W/3,000lm/3,000K	12.7	9.135.8042.41-2

power reduction without pilot-line, dimming level and time according to customer's request 9.135.xxxx.41-2-93

power reduction with pilot-line, dimming level and logic according to customer's request 9.135.xxxx.41-2-94

- accessory:** galvanised steel and powder coated in DB 703
- MA1576150** single bracket 15°, \varnothing 76mm 2.6 9.925.0017.764
 - ZMA 1576150** double bracket 15°, \varnothing 76mm 2.9 9.925.1529.764
 - LS DA 1** back light shield made of plastic 0.01 2.914.8301.17

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice.09.2022

