

bollard


CE | Ⓢ | □ | EN 60598-2-3 | IP 65 | IK 10 | CRI 70 | 220V – 240V / 50Hz – 60Hz



# BURKHARD P I DA LED



height of lamp: 900mm  
 light standards: low lighting requirements  
 lamp: incl. 1 DA LED module, easy to replace  
 colour temperature: 3.000K warm white or 4.000K neutral white  
 surge protection: 10kV  
 LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency  
 LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management  
 light control: at extra cost: power reduction, dimming, DALI  
 optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology  
 light distribution: narrow and wide beam  
 luminaire head: steplessly adjustable, made of die cast aluminium with short bracket made of hot dip galvanised steel; powder coated; post luminaires incl. elegant stainless steel hose for cable protection  
 tube: made of hot dip galvanised steel without door; powder coated  
 colour: DB 703; other RAL or DB colour without extra cost on request  
 glazing: clear toughened glass glazing, to be hinged down  
 wiring: luminaire head completely wired; via a clamp within the luminaire head  
 installation: with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root  
 accessory: cable, bolt-on root with screws, accessory ring, back light shield for non-glare on the rear side – to be ordered separately  
 application areas: schools, kindergarten, squares, parks, pedestrian zones, car parks, hotels



narrow and wide beam  
 area: 10m x 10m

lamp	kg	product code
DA+ 2x4/268 LED 6W/1.100lm/3.000K	23,9	6.885.8107.05268-3
DA+ 2x4/268 LED 13W/2.000lm/3.000K	23,9	6.885.8117.05268-3
DA+ 2x4/268 LED 6W/1.150lm/4.000K	23,9	6.885.8107.05268
DA+ 2x4/268 LED 12W/2.050lm/4.000K	23,9	6.885.8117.05268
power reduction without pilot-line, dimming level and time according to customer's request		6.885.xxxx.05268-93
power reduction with pilot-line, dimming level and logic according to customer's request		6.885.xxxx.05268-94
<b>accessory:</b>		
bolt-on root – hot dip galvanised steel, incl. screws <b>G180/400</b>	3,3	9.900.0011.00
accessory ring – stainless steel, powder coated <b>Z185</b>	0,3	9.900.0010.27

class II at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 10.2022

