

post top luminaire

# ERICH II PL-LS LED



- recom. pole height: 3.00m – 6.00m
- light standards: low and medium lighting requirements
- lamp: incl. 2 PL-LS LED modules
- colour temperature: 2,700K warm white; 3,000K or 4,000K on request
- surge protection: 10kV
- LED gear: incl. 2 drivers, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency
- LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management
- light control: at extra cost: power reduction, dimming or Zhaga socket
- optical system: vertically mounted directed PL-LS LED modules for wide spacings; opal diffused cover tube for each PL-LS-LED module; diffuse
- light distribution: symmetrical; asymmetrical with back shield on request
- luminaire head: incl. canopy made of aluminum, with white special coating on the underside; incl. pole mounting; powder coated
- colour: DB 703; other RAL or DB colour without extra cost on request
- glazing: 4-part cover made of textured PMMA (bark type) completely wired; incl. cable until access door (please specify pole height when ordering)
- wiring:
- installation: for post top  $\varnothing$  76mm or  $\varnothing$  60mm
- accessory: pole, pole accessories – to be ordered separately
- application areas: residential and local distribution roads, car parks, schools, hotels, factory premises, paths, squares, parks

lamp	kg	product code
<b>for post top <math>\varnothing</math> 76mm</b>		
PL-LS LED 24W/4,000lm/2,700K	16.7	9.055.2638.19-88
<b>for post top <math>\varnothing</math> 76mm</b>		
PL-LS LED 24W/4,000lm/2,700K	16.7	9.055.2638.19-88-60
power reduction without pilot-line, dimming level and time according to customer's request		9.055.xxxx.19-88-93
power reduction with pilot-line, dimming level and logic according to customer's request		9.055.xxxx.19-88-94

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 03.2026

