


post top luminaire



EVA II LLM-DA LED



- recom. pole height: 3.00m – 5.00m
- light standards: for low, medium and high lighting requirements
- lamp: incl. 1 glare-free LLM-DA LED module
- colour temperature: 3.000K warm white or 4.000K neutral white
- surge protection: 10kV
- LED gear: electronic driver, up to 100.000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for operation with central battery systems
- LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 / B10 for minimum maintenance costs due to an excellent thermal management
- light control: at extra cost: dimming; power reduction or CLEVER LIGHT
- optical system: computer-optimised reflector made of highest grade aluminium, polished and anodised for horizontally mounted LLM-DA LED module
- light distribution: wide beam
- luminaire head: incl. canopy ø 600mm made of aluminium with a special underside finish; base made of cast aluminium; powder coated
- colour: DB 703; other RAL or DB colour without extra cost on request
- glazing: polycarbonate, clear, UV-stabilised
- wiring: completely wired; via a plug and socket connector below the luminaire head
- installation: for post top ø 60mm or ø 76mm
- accessory: cable, column, pole accessories – to be ordered separately
- application areas: residential and local distribution roads, car parks, schools, hotels, factory premises, paths, squares, parks



wide beam
height: 4.50m; area: 30m x 30m

lamp	kg	product code
for post top ø 60mm		
LLM-DA LED 9W/1.100lm/3.000K	9,0	9.898.9017.05-2
LLM-DA LED 16W/1.800lm/3.000K	9,0	9.898.9008.05-2
LLM-DA LED 26W/3.000lm/3.000K	9,0	9.898.9042.05-2
for post top ø 76mm		
LLM-DA LED 8W/1.100lm/4.000K	9,0	9.898.9015.05-2
LLM-DA LED 15W/1.800lm/4.000K	9,0	9.898.9005.05-2
LLM-DA LED 24W/3.000lm/4.000K	9,0	9.898.9035.05-2
		9.898.xxxx.07-2

power reduction without pilot-line, dimming level and time according to customer's request 9.898.xxxx.0x-2-93

power reduction with pilot-line, dimming level and logic according to customer's request 9.898.xxxx.0x-2-94

class II at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 06.2022

