

luminous column

KATHLEEN L I/10 LIN LED



total height: 4.00m
 light standards: medium lighting requirements
 lamp: incl. 1 LIN LED module
 colour temperature: 3,000K warm white or 4,000K neutral white
 surge protection: 10kV
 LED gear: incl. 4DIM driver, up to 100,000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible
 LED life expectancy: up to 80.000 hours for minimum maintenance costs due to an excellent thermal management
 light control: at extra cost: dimming
 optical system: diffuse
 light distribution: symmetrical
 luminaire head: with cap made of aluminium, powder coated;
 luminaire body: straight tubular column made of aluminium with 2 access doors for cable junction box and driver; powder coated
 colour: DB 703; other RAL or DB colour without extra cost on request
 glazing: PMMA RESIST, opal, high-impact resistant
 wiring: completely wired; incl. cable until access door
 installation: with flange plate to be screwed on a concrete foundation on site or on an additional bolt on root or with root to be set into the ground
 accessory: cable junction box, tube accessories, bolt-on root with screws – to be ordered separately
 application areas: for promenades, parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distributor roads, paths, cycle lanes, squares, car parks, shopping center, pedestrian zones

lamp	kg	product code
LIN LED 33W/5.000lm/3.000K	36.3	9.005.8103.31B
LIN LED 29W/5.000lm/4.000K	36.3	9.005.8103.41B
accessory:		
bolt-on root – hot dip galvanised steel G300/1000	14,0	9.900.0022.02
accessory ring – stainless steel, powder coated Z305/2	0,8	9.900.0008.73

class II - at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 10.2022

