

pillar mounted luminaire  
**KORA I LED**

CE | Ⓢ | Ⓜ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz



total height:	0.24m
light standards:	low lighting requirements
lamp:	incl. LED RGBW module or PL-Cube LED
colour temperature:	3.000K warm white or 4.000K neutral white
LED gear:	ballast integrated in lamp
LED life expectancy:	up to 50.000 hours/ L70/ B10
light control:	RGBW with individual settings for scenes and sequences
optical system:	homogeneous, diffuse
light distribution:	symmetrical; 4 windows
luminaire body:	detachable; made of a square stainless steel design shadow gap, powder coated or brushed and passivated
colour:	RAL or DB
glazing:	PMMA RESIST, opal, high-impact resistant; with decorative grille
wiring:	completely wired; suitable for loop in and loop out
installation:	with integrated flange plate to be screwed on a concrete foundation on site
accessory:	cable, sensor and remote control – to be ordered separately
application areas:	very robust design element as terrain mark or as seating; for hotels, factory premises, schools, home for elderly people, squares, parks, private gardens, pedestrian zones

lamp	kg	product code
<b>powder coated</b>		
PL-Cube LED 12W/1.100lm/3.000K	25,0	9.825.9006.00-3
PL-Cube LED 12W/1.100lm/4.000K	25,0	9.825.9006.00
LED 23W/845lm/RGBW	25,0	9.825.9007.00
<b>brushed and passivated</b>		
PL-Cube LED 12W/1.100lm/3.000K	25,0	9.825.9006.30-3
PL-Cube LED 12W/1.100lm/4.000K	25,0	9.825.9006.30
LED 23W/845lm/RGBW	25,0	9.825.9007.30

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 05.2018

