

bollard with light and power unit

LOTTA P I LED 1S

CE | ⊕ | □ | EN 60598-2-3 | IP 65 | IK 08
220V – 240V / 50Hz – 60Hz



total height: 0.90m
 light standards: low lighting requirements
 lamp: incl. TAB-LL3 LED modul
 colour temperature: 4.000K neutral white or 3.000K warm white
 LED gear: electronic driver, up to 85,000 hours/ B10; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux the same over the entire life time

LED life expectancy: up to 50,000 hours/ L70/ B 10
 light control: at extra cost: dimming
 optical system: diffuse
 light distribution: symmetrical (4 windows)
 luminaire body: made of a square stainless steel profile with access door for incl. cable junction box and 1 pc. socket 16A / 1p / 230V; fuses not included; powder coated

colour: RAL or DB
 glazing: PMMA RESIST, opal, high-impact resistant
 wiring: completely wired; incl. cable junction box: incl. cable until the cable junction box for cable up to 5x10mm², 3 cables up to 5x6mm²

installation: with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root
 accessory: bolt-on root – to be ordered separately
 application areas: solid line for boulevards, fair grounds, hotels, schools, factory premises, squares, parks, pedestrian zones, home for elderly people

lamp	kg	product code
------	----	--------------

TAB-LL3 LED 14.9W/1,532lm/3,000K	13,4	6.810.9123.114-G30K1ST
TAB-LL3 LED 14,9W/1.632lm/4.000K	13,4	6.810.9123.114-G40K1ST

power reduction without pilot-line, dimming level and time according to customer's request 6.810.xxxx.114-P-G40K1ST

power reduction with pilot-line, dimming level and logic according to customer's request 6.810.xxxx.14-G40K1ST-SDU

accessory:
 bolt-on root – hot dip galvanised steel, incl. screws
Q180/400 4,8 9.900.0018.02

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 06.2018

