

spot luminaire with bell-shaped heads

MAJA I DA LED



total height: 4.50m
 light standards: for medium and high lighting requirements
 lamp: incl. 2 DA (2x4) LED modules per luminaire head
 colour temperature: 3,000K warm white or 4,000K neutral white
 surge protection: 10kV
 LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency
 LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90 /B10 for minimum maintenance costs due to an excellent thermal management
 light control: at extra cost: power reduction, dimming, DALI
 light distribution: symmetrical
 luminaire head: 3 luminaire heads, adjustable; made of aluminum, with decorative bracket made of stainless steel, powder coated
 pole: tubular conical column, made of hot-dip galvanised steel, with door for cable junction box; powder coated DB 703; other RAL or DB colour without extra cost on request
 colour: PMMA RESIST, clear, high-impact
 glazing: completely wired; incl. cable until access door
 wiring: with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root; on request: with root to be set into the ground
 installation: cable junction box, pole accessory – to be ordered separately
 accessory: squares, boulevards, playgrounds, schools, home for elderly people, hotels, resorts, factory premises, car parks

lamp	kg	product code
------	----	--------------

3 luminaire heads - 4,50m		
each DA LED 13W/2.200lm/3.000K ⁽²⁾	74,4	6.200.8207.058-3-031-F
each DA LED 15W/2.500lm/3.000K ⁽²⁾	74,4	6.200.8210.058-3-031-F
each DA LED 20W/3.200lm/3.000K ⁽²⁾	74,4	6.200.8212.058-3-031-F
each DA LED 26W/4.000lm/3.000K ⁽²⁾	74,4	6.200.8227.058-3-031-F
each DA LED 12W/2.300lm/4.000K ⁽²⁾	74,4	6.200.8207.058-031-F
each DA LED 14W/2.600lm/4.000K ⁽²⁾	74,4	6.200.8210.058-031-F
each DA LED 19W/3.300lm/4.000K ⁽²⁾	74,4	6.200.8212.058-031-F
each DA LED 25W/4.100lm/4.000K ⁽²⁾	74,4	6.200.8227.058-031-F

power reduction without pilot-line, dimming level and time according to customer's request 6.200.xxxx.058(-3)-031-F-93

power reduction with pilot-line, dimming level and logic according to customer's request 6.200.xxxx.058(-3)-031-F-94

accessory:
 bolt-on root – hot dip galvanised steel, incl. screws
G240/1000 11,5 9.900.0012.10L

class II at extra cost (add "S" at the end)
 Technical specifications are subject to change without notice. 09.2025

