

bollard

PETRA PA I/600 LED

PETRA PA III/600 LED



- total height: 0.60m
- light standards: for low lighting requirements
- lamp: incl. GLE LED, easily replaceable
- colour temperature: 2.700K warm white
- gear: ballast integrated in lamp
- LED life expectancy: up to 25.000 hours/ L70
- light control: at extra cost: dimming
- optical system: direct beam, glare-free
- light distribution: asymmetrical or symmetrical
- light emission: 1 or 2 sides
- luminaire body: made of aluminium; powder coated
- colour: DB 703; other RAL or DB colour without extra cost on request
- glazing: PMMA RESIST, opal, high-impact resistant
- wiring: completely wired, via a plug and socket connector below the luminaire head
- installation: tube with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root; delivery in one piece; lamp separately packed
- accessories: cable, bolt-on root incl. screws and accessory ring – to be ordered separately
- application areas: parkways, schools, hotels, factory premises, paths, squares, beer gardens, camping-sites

lamp	socket	kg	product code
PETRA PA I/600 - light emission at 1 side			
GLE LED 7W/806lm/2.700K	E27	2,5	9.883.9002.00160AL
PETRA PA III/600 - light emission at 2 sides			
GLE LED 7W/806lm/2.700K	E27	2,3	9.883.9002.00360AL
accessory:			
bolt-on root incl. screws			
G180/400		3,3	9.900.0011.00
accessory ring, powder coated in DB 703			
Z180/2		0,2	9.900.0010.25

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 06.2025

