

The Marram Grass POA L IV DA LED

CE | Ⓢ | Ⓜ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz



- total height: 4.00m
- light standards: for low and medium lighting requirements
- lamp: incl. 4 DA+ (2x2) LED modules
- colour temperature: 3.000K warm white or 4.000K neutral white
- surge protection: 10kV
- LED gear: incl. driver, up to 100,000 hours; with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for emergency
- LED life expectancy: 65,000 hours/ L100/ B10; 100,000 hours/ L90/ B10 for minimum maintenance costs due to an excellent thermal management
- light control: at extra cost: power reduction or dimming
- optical system: diffuse
- light distribution: asymmetrical wide beam
- luminaire body: top made of corrosion resistant cast aluminium and tapered bent pole with access door for cable junction box made of hot dip galvanised steel; powder coated
- colour: DB 703; other RAL or DB colour without extra cost on request
- glazing: PMMA RESIST, satined, high-impact
- wiring: incl. cable until access door
- installation: with root to be set into the ground
- accessories: cable junction box, foundation – to be ordered separately
- application areas: promenades, parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distributor roads, paths, cycle lanes, squares, car parks, pedestrian zones

lamp	kg	product code
DA+ (2x2) LED 26W/4.000lm/3.000K ⁽⁴⁾	65	6.111.8406.04176g-3
DA+ (2x2) LED 24W/4.100lm/4.000K ⁽⁴⁾	65	6.111.8406.04176g

(4) 4 modules
class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 01.2024

