

post top luminaire
RICHARD VIII DA LED

CE | Ⓢ | Ⓜ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz



recom. pole height: 3.00m – 5.00m
 light standards: for medium lighting requirements
 lamp: inkl. 2 DA+ (2x4) LED modules
 colour temperature: 4.000K neutral white or 3.000K warm white
 surge protection: 10kV
 LED gear: incl. 4DIM driver, up to 100,000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible
 LED life expectancy: up to 100,000 hours, 50,000 hours/ L100/ B10 for minimum maintenance costs due to an excellent thermal management
 light control: at extra cost: power reduction, dimming or CLEVER LIGHT
 optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology
 light distribution: asymmetrical wide beam or symmetrical; others on request
 luminaire head: canopy made of aluminium; base made of corrosion-resistant cast aluminium; powder coated
 colour: RAL or DB
 glazing: PMMA RESIST, clear, high-impact
 wiring: via a plug and socket connector outside the luminaire head; easy installation
 installation: for top entry \varnothing 76mm
 accessory: column, cable, pole accessories, back light shield, changeover relay, address block, - to be ordered separately
 application areas: for parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, paths, cycle lanes, squares, car parks, shopping center, pedestrian zones

lamp	kg	product code
asymmetrical wide beam		
DA+ 028 LED 12W/2,300lm/4,000K	10,1	4.892.8207.187028
DA+ 028 LED 14W/2,600lm/4,000K	10,1	4.892.8210.187028
DA+ 028 LED 19W/3,300lm/4,000K	10,1	4.892.8212.187028
DA+ 028 LED 25W/4,100lm/4,000K	10,1	4.892.8227.187028
DA+ 028 LED 15W/2,200lm/3,000K	10,1	4.892.8207.187028-3
DA+ 028 LED 17W/2,500lm/3,000K	10,1	4.892.8210.187028-3
DA+ 028 LED 23W/3,200lm/3,000K	10,1	4.892.8212.187028-3
DA+ 028 LED 30W/4,000lm/3,000K	10,1	4.892.8227.187028-3
symmetrical		
DA+ 058 LED 12W/2,300lm/4,000K	10,1	4.892.8207.187058
DA+ 058 LED 14W/2,600lm/4,000K	10,1	4.892.8210.187058
DA+ 058 LED 19W/3,300lm/4,000K	10,1	4.892.8212.187058
DA+ 058 LED 25W/4,100lm/4,000K	10,1	4.892.8227.187058
DA+ 058 LED 15W/2,200lm/3,000K	10,1	4.892.8207.187058-3
DA+ 058 LED 17W/2,500lm/3,000K	10,1	4.892.8210.187058-3
DA+ 058 LED 23W/3,200lm/3,000K	10,1	4.892.8212.187058-3
DA+ 058 LED 30W/4,000lm/3,000K	10,1	4.892.8227.187058-3

power reduction without pilot-line, dimming level and time according to customer's request 4.892.82xx.187xxx(-3)-93

power reduction with pilot-line, dimming level and logic according to customer's request 4.892.82xx.187xxx(-3)-94

accessory:
back light shield LS DA 1 2.914.8301.17

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 01.2022

