

# ring luminaire ZOE II BX LED

CE | Ⓢ | Ⓜ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz



total height: 4.50m  
 light standards: low, medium and high lighting requirements  
 lamp: incl. BX LED module  
 colour temperature: 3.000K warm white; 4.000K neutral white on request  
 LED gear: electronic driver, up to 50,000 hours  
 LED life expectancy: up to 50,000 hours/ L70 for minimum maintenance costs due to an excellent thermal management  
 optical system: diffuse  
 light distribution: symmetrical  
 luminous ring: made of aluminium profile, powder coated  
 column: curved rectangular and square profile support as special column, made of stainless steel V2A (304); with access doors incl. cable junction box; powder coated  
 colour: DB 703; other RAL or DB colour without extra cost on request  
 glazing: PMMA RESIST, satined, high-impact resistant  
 wiring: completely wired, incl. cable until access door  
 installation: with flange plate to be screwed on a necessary bolt-on root  
 accessory: bolt-on root – to be ordered separately  
 application areas: parkways, boulevards, schools, kindergardens, hotels, home for elderly people, factory premises, special squares

lamp	kg	product code
LED BX 84W/11.600/3.000K	102,0	9.015.8005.10

**necessary accessory:**  
 bolt-on root – hot dip galvanised steel, incl. screws  
**Q400/LS300/1200** 28,0 9.900.0020.00

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 10.2024

