

ring luminaire ZOE I RGBW LED ZS

CE | Ⓢ | EN 60598-2-3 | IP 65 | 220V – 240V / 50Hz – 60Hz

Zhaga



total height: 4.50m
 light standards: low, medium and high lighting requirements
 lamp: incl. RGBW LED modules
 colour temperature: 3,000K warm white; 4,000K neutral white on request
 LED gear: incl. drivers inside the pole, 50,000 hours
 LED life expectancy: up to 50,000 hours/ L70 for minimum maintenance costs due to an excellent thermal management
 light control: incl. 1 standardised Zhaga socket on the pole; oriented downward to control individually RGBW via an factory-installed CLEVER LIGHT HUB-GPS ST 203-C
 optical system: diffuse
 light distribution: symmetrical
 luminous ring: light ring consisting of three aluminium segments; powder coated
 column: 3 curved, tapered rectangular profile struts made of stainless steel V2A (304); each with 2 pole doors including cable junction box and an additional maintenance door; powder coated
 colour: DB 703; other RAL or DB colour without extra cost on request
 glazing: PMMA RESIST, satined, high-impact resistant
 wiring: completely wired, incl. cable until access door with flange plate to be screwed on a necessary bolt-on root
 installation: bolt-on root – to be ordered separately
 accessory: bolt-on root – to be ordered separately
 application areas: parkways, boulevards, schools, kindergardens, hotels, home for elderly people, factory premises, special squaress

lamp	kg	product code
LED RGBW: 492W/45,720lm Red: max. 5,760lm Green: max. 15,840lm Blue: max. 3,780 lm White: max. 20,340 lm	353.0	9.015.8042.30-RGBW-ZSu

accessory:
 bolt-on root – hot dip galvanised steel, incl. screws
G600/1200 70.0 9.900.0026.10

class II – at extra cost (add "S" at the end)

Technical specifications are subject to change without notice. 03.2026

